

Serenade

Chemical Specification Sheet

ITEM# 122504SYM

Harmony High Solids Floor Finish

Ultra Compatible Low Odor Finish • For Extreme Traffic • Unsurpassed Durability & Protection

Brilliant, high-gloss, thermoplastic finish & sealer provides the optimum in durability and wear for all floor types including resilient tile, concrete and terrazzo. High solids formula allows for fewer coats to achieve superior results. Ideal for medium and low maintenance systems, "Harmony High Solids Floor Finish" will withstand the toughest conditions and can be easily repaired using a restorer.

DIRECTIONS:

Application:

- 1- Thoroughly strip floor using a Symphony Stripper.
- 2- Floor surface must be clean, dry and free of residue before applying finish
- 3- Apply product using uniform coats with a microfiber pad, rayon or synthetic mop.
- 4- Allow each coat to dry thoroughly before adding additional coats. The recommended number of coats is 3-4 and dry time is approximately 25-30 minutes.

Maintenance:

- 1- Dust mop and damp mop floor regularly.
- 2- Clean floor using a Symphony Allegro Neutral Cleaner.
- 3- When floor needs added gloss, renew with Symphony Resolution Mop-On Gloss.

Recoating:

- 1- Dust mop or sweep floor.
- 2- Using a blue or green pad, top scrub with Symphony Concerto Multi-Surface Cleaner.
- 3- Apply 1-2 coats and allow drying.

Este acabado deja una brillante, lustroso sellado termoplástico que proporciona el grado óptimo en durabilidad y disminuya el desgaste para todo tipos de pisos incluyendo: azulejos, concreto y mosaico. Su fórmula de alto sólidos permite que pocas capas logren resultados superiores. Harmony trabaja en las condiciones más resistentes y se puede restaurar con un restaurador.

INSTRUCCIONES DE USO:

Aplicación:

- 1- Limpie a fondo el piso usando el Removedor de Pisos Brillante Bruto.
- 2- El piso debe estar limpio, seco y libre de residuos antes de aplicar este producto.
- 3- Aplique el producto usando capas uniformes con una almohadilla de micro fibra, rayón o trapeador sintético.
- 4- Deje secar completamente antes de aplicar capas adicionales. Se recomiendan de 3 a 4 capas y el tiempo de secado es aproximadamente de 25 a 30 minutos.

Mantenimiento:

- 1- Trapee el piso regularmente.
- 2- Limpie el piso usando el Limpiador Neutral Brillante.
- 3- Cuando el piso necesite más brillo, use el renovador de Rociador Brillante.

Recubrimiento:

- 1- Barra o trapee el piso.
- 2- Usando la almohadilla azul o verde, friegue la superficie con el limpiador Especial Brillante Verde.
- 3 - Aplicar las capas 1-2 y dejar secar.



HMIS/NFPA Hazard Rating:

HEALTH	1
FLAMMABILITY	0
REACTIVITY	0

Degree of Hazard:

0- Least 1- Slight 2- Moderate 3- High 4- Extreme

Stability: Shall remain stable when stored under normal conditions in original unopened containers. Do not allow to freeze.

pH*: 8.5 - 9.5

Specific Gravity: 1.02

VOC: N/A

*as determined by a glass electrode pH meter as a concentrate. For industrial and institutional use only, not for retail sale. See SDS for complete product specifications.

Serenade Solutions, LLC



2040 Junction Ave.
San Jose, CA 95131
www.serenadesolutions.com